

star HSP7000



- Ultra high speed receipt printing (250mm/s)
- Built-in MICR Reader Standard on HSP7743 & HSP7643
- Affordable Price: Key Functions & High Quality Graphics
- Check Validation and Form Printing
- One Pass MICR + Check Validation (HSP7643)
- One Pass MICR + Check Endorsement (HSP7743)

The Functions You Need At The Price You Can Afford

Star Micronics is proud to announce another addition to its extensive product line of POS printers. The multifunction (hybrid), HSP7000.

The HSP7000 is designed to assist and empower users who want to extend the capabilities of their current system.

Star Micronics has developed the best value solution for markets that utilize the three (3) primary functions of a multifunction printer:

- Read the check's MICR reliably
- Endorse checks without jams
- Print a receipt as fast as possible

The HSP7000 combines key features from Star's celebrated range of products, including the speed and reliability of the market leading TSP700II Series, and the engine from the high speed SP700 dot matrix printer. Star is bringing over 30 years of "know-how" in POS to the HSP7000; resulting in customers receiving the features they need with the reliability they demand, minus the overhead of unnecessary features and associated cost.



Easy Paper Loading



Check MICR Reader



Validation Station



Slip/Endorsement Station



Star Micronics Southeast Asia

Tel. +66(0)2-631-1161-2 Sales@star-m.co.th

@ 2015 Star Micronics Southeast Asia

All Rights Reserved. All trademarks are property of their respective owners. Specifications are subject to change without notice.

www.starmicronics.co.th

HSP7000 Specifications

| The Functions You Need At the Price You Can Afford | | |
|---|--|---|
| Features | Hardware Ultra Fast Receipt Printing (250mm/s) "Drop-In & Print" Clamshell Design Quick Check Processing w/ MICR Reader Fast and Easy Validation Reliable Guillotine Cutter Small Footprint PDF417 Barcode Support (Receipt Station) Double Resolution Mode Support Swappable Communication Interfaces Digitally Signed Driver (WHQL) Recessed Cable Connections | Software Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Configuration Setup Utility Ethernet Interface Setup Utility Create a Virtual Serial Port for Legacy Applications StarIO SDK |
| Connectivity Note: Connections in bold are supported; grayed-out connection types may be supported by special request. | 9-Pin Serial 25-Pin Serial Parallel USB Powered USB Ethernet Wireless LAN Dual 9-Pin Serial/USB | Virtual Serial Port to USB Virtual Serial Port to Ethernet Virtual TCP/IP Port |
| Drivers | Windows® XP Vista (32 bit / 64 bit) Windows 8 , 7 (32 bit / 64 bit) Server 2008 (32 bit / 64 bit) CE / Windows Server 2012 (32 Bit / 64 Bit) XP Embedded POS for .NET | OPOS™ JavaPOS™ USB Vendor Class Linux™ CUPS Mac OS X CUPS |
| What's Included | Installation CD (Printer Driver / Utility / Manuals) Setup Sheet Interface Cover Paper Guide for 76mm / 58mm Width | Power Switch Cover Ferrite Core Ink Ribbon Cartridge Start Up Paper Roll |
| Options | External Power Supply (PS60A) Putty or Gray Color | MICR + Endorsement in One Pass (HSP7743) MICR + Validation in One Pass (HSP7643) No MICR Version (HSP7543) |
| Technical Specifications Thermal Receipt Station | Print Method : Direct Thermal Print Speed : 250mm/s Paper Width : 80mm / 76mm / 58mm Paper Thickness : 0.06 to 0.08mm Paper Diameter : Max 83mm | Resolution: 203 dpi MCBF: 60 Million Lines Cutter: 1.5 Million Cuts Emulation : Star Line Mode, ESC/POS™ |
| Slip/ Endorsement Station | Print Method : 9 Pin Impact Dot Matrix Print Speed : 4.82lps (40 columns) Columns : 60/45 Paper Width : 68mm to 230mm Paper Length : 75mm to 297mm | Paper Thickness : 0.09 to 0.2mm (Single-Ply Paper) Less than 0.31mm (Multi-Ply Paper) Copy Capacity : Original + 3 copies MCBF : 37 Million Lines Emulation : Star Mode, ESC/POS™ |
| Validation Station | Lines : Max 8 Lines | |
| MICR Reader | Character Set : E13B / CMC-7 | |
| | Power : DC24V Dimensions : W=186mm, H=177mm, D=296mm | Weight : 4.6kg |