









# TSP654IIHI01X with CloudPRNT

Star Micronics presents CloudPRNT Solution, an Innovative Technology Tools for enabling users to print to Star printers directly through the cilent's cloud service.

CloudPRNT will work with the online ordering service to store and create print jobs, and communicate status with the printer. Cloud ordering services will post orders using a JSON format while the Star CloudPRNT printer will pull these orders on a defined interval.

Star's CloudPRNT technology provides benefits to both restaurant and retail stores alike by eliminating the need for an extra tablet to send an online order to the printer. Instead, the ordering service will be able to communicate directly to the printer. The store owner or service providers do not need to maintain an SSL certificate for this CloudPRNT printers since the printer communicates with the server as a client.

LAN/WIFI remote printing direct from your web server to any printer any where in the world. (More information please contact us)















# Optional - Melody Buzzer Optional - POS Device

# TSP654IIHI01X with CloudPRNT

### Printer Specifications

Feature - Hardware: · High performance printing speed 300mm per second

· "Drop In & Easy Paper Loading"

High Quality 203 dpi print quality with barcode
Including 2D for receipt, coupon and ticketing
Compact Horizontal and Vertical Footprint

Auto Cutter as Standard (Partialcut)

Operating Systems : Conectivity : Options : iOS, Android and WindowsLan and Wi-Fi (by USB WiFi Adapter)Splash Proof Cover (SPC-T100)

· Buzzer (BU01-24A)

· Melody Buzzer mC-Sound (MSC10)

· Vertical Stand (VS-T650)

## Technical Specifications

Print Method : Direct Thermal
Print Resolution : 230 dpi
Print Speed : 300 mm/sec

Paper Width: 80 mm / 58 mm (Paper Guide)

 Print Width:
 72 mm / 50.8 mm

 Paper Thickness:
 0.053 - 0.085 mm

Paper Roll Diameter : 83 mm

Dimensions : 140 (W) x 132 (H) x 203.5 (D) mm

Weight: 1.60kg

Auto-Cutter: Partial-Cut (Guilotine)
Power Supply: External Option PS60
Sensor: Cover Open Sensor

Barcode: 1D Barcode(UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, CODE39,

ITF, CODABAR) and 2D Barcode (QRCode, PDF47, GS1)

Reliability

Printer MCBF: 60 million lines
Printer Head: 100 km
Cutter: 2 million cuts

