

star HSP7000

The Function You Need at The Price You can Afford





Star Micronics is proud to announce another addition to its extensive product line of POS printers. The multifunction (hybrid), HSP7000.

The HSP7000 is designed to assist and empower users who want to extend the capabilities of their current system.



Printer Feature

- High Speed 250mm/s thermal receipt printer combined with high quality 9-pin matrix cheque / validation printer
- "Drop-In & Print" easy paper loading
- High resolution 203 dpi output for fast, superior quality logo / barcode receipt output
- Auto status back for paper loading, sensor reporting etc.



Printer Specification



Swappable Interface



Easy Paper Loading



Slip/Validation

Features	Hardware Ultra Fast Receipt Printing 250mm/s Easy Paper Loading "Drop-In and Print" Reliable Guillotine Cutter Swappable Communication Interfaces Fast and Easy Validation Quick Check Processing with MICR Reader Sensor Reporting (Open Sensor, NE Sensor etc.) Slip Printing (3 Copies) Format Printing (Thai, English, Number & Symbols) Compatible with USB Port Printer Status Reporting through Computer	Software Available on Windows Server 2019 Available on Windows 10 (32bit/64bit) Logo Utility (Store Logo, Coupon & Graphics) StarIO SDK Memory Switch Configuration Setup Utility
Connectivity	25-Pin Serial Interface (RS232c) Parallel Interface USB Interface Power USB (Option) Ethernet Interface Dual 9-Pin Serial/USB Interface	Virtual Serial Port to USB
Specification Thermal	Printing Method : Direct Thermal Lind Printing Printer Speed : 250 mm/s Paper Width : 80 mm / 72 mm Print Width : 76 mm / 68 mm / 58 mm / 51 mm Paper Diameter : 80 - 102 mm Paper Thickness : 0.065 - 0.085 mm Sensor : Black Mark, Cover Open, Paper End & Near End MCBF : 60 million lines Print Head : 50 kilometers Auto-Cutter : 1.5 million cuts	
Specification Dot Matrix	Printing Method : 9-Pin Bidirectional Logic Seeking Printer Speed : 4.82 LPS (40 Column) / 8.9 LPS (16 Column) Paper Width : 230 mm Print Width : 84.5 mm Paper Length : 75 - 297 mm Paper Thickness : 1Ply 0.09 - 0.20 mm / 4Ply 0.09 - 0.31 mm Paper Loading : Intelligent Font Loading Multiples Copies : Original + 3 Copies Ribbon Cartridge : RC7KB Validation : Maximum 8 Lines Reliability : 37 million lines	
Specification Printer Unit	Resolution : 203 dpi (8 dot/mm) Dimension (WxDxH) : 186 x 296 x 177 mm Emulation : Star Mode & ESC/POS Weight : 4.6 kg Power Supply : 24VDC	
Software Support Driver	Windows XP (32bit) Windows Vista (32bit/64bit) Windows 7 (32bit/64bit) Windows 10 (32bit/64bit) Windows Server 2008 (32bit/64bit) Windows Server 2019 (32bit/64bit) Windows XP Embedded Windows POSReady 2009	OPOS JavaPOS USB Vendor Class Linux Mac OS X StarIO SDK (for iOS, Android and Blackberry)
What's Included	Set Up Guide Paper Guide Roll Paper 2 Ribbon Cartridge Power Cable Adapter PS60A	

