

## How to Enable or Disable Taken Sensor for printer TSP650IISK model (by Operation Manual)

1. Power printer [ON] and open the paper cover.
2. Press and hold the [FEED] button for 5 seconds or until the (red) ERROR light flashes rapidly (0.5 sec intervals)
3. To disable or enable the Taken Sensor, press the [FEED] button until the desired setting is displayed,

Flashing in GREEN = Enabled and Flashing in RED = disable then close the paper cover.



**Enable (Valid)**



**Disable (Invalid)**

4. The printer will automatically print a self-test indicating the new status.

```
-- Memory Switch Detail --
<0>4 = Character Mode: StandardU3.0
<1>9 = Top Margin: Default
<1>4 = Zero Style: Normal Zero
<1>3-0= Inter. Char: USA
<2>F = Refresh Mode: Valid
<2>D = Speed Down@Barcode: Yes
<2>C = 180 Rotation: Invalid
<2>A,8= Print Start Control: Page
<2>7 = Print Pass: Special
<2>5,4= Print Speed: Normal
<3>F-8= Page: Normal
<3>4 = ANK Pitch: 12 dot
<3>1 = <CR>: Ignore
<3>0 = Feed Pitch: 4mm
<4>2-0= Printable Area: 72mm
<8>3 = H-Paper Reduction: Invalid
<8>2 = V-Paper Reduction: Invalid
<A>F-D= HoldPrintTimeout : Invalid
<A>C = HoldPrintReminder: Invalid
<A>1 = HoldPrintStatus : Valid
<A>0 = HoldPrint : Valid
```

```
-- Memory Switch Detail --
<0>4 = Character Mode: StandardU3.0
<1>9 = Top Margin: Default
<1>4 = Zero Style: Normal Zero
<1>3-0= Inter. Char: USA
<2>F = Refresh Mode: Valid
<2>D = Speed Down@Barcode: Yes
<2>C = 180 Rotation: Invalid
<2>A,8= Print Start Control: Page
<2>7 = Print Pass: Special
<2>5,4= Print Speed: Normal
<3>F-8= Page: Normal
<3>4 = ANK Pitch: 12 dot
<3>1 = <CR>: Ignore
<3>0 = Feed Pitch: 4mm
<4>2-0= Printable Area: 72mm
<8>3 = H-Paper Reduction: Invalid
<8>2 = V-Paper Reduction: Invalid
<A>F-D= HoldPrintTimeout : Invalid
<A>C = HoldPrintReminder: Invalid
<A>1 = HoldPrintStatus : Invalid
<A>0 = HoldPrint : Invalid
```

5. Power printer [OFF] and [ON] to save settings.