




SK1-311 three-inch series provides dependable, maintenance-free, high reliability printers that have a fast print speed of 250mm/sec with 203 dpi resolution.

The printers come with 2 model that is horizontal orientation and vertical orientation. Both of them have various options for match with any kiosk solution.

All SK1-311 models come with Serial RS-232C and Mini-USB interfaces which integrate with many commonly used kiosk solutions.

















Adjustable

Paper Holder





SK1-311 Specifications

Printer Model	SK1-311	
Printer Method	Direct Thermal Line Printing	
Emulation	StarPRNT & ESC/POS	
Print Speed	Max. 250 mm/second	
Resolution	203 dpi (8 dot/mm)	
Print Width	80mm / 72mm / 56mm /54mm	
Paper Specifications	Туре	Thermal Paper Roll
	Paper Width	83mm / 80mm / 60mm / 58mm
	Roll Diameter	Max. Ø 120mm (254mm with option)
	Thickness	59 ~ 150 μm
Auto-Cutter	Partial cut (Leave center point) / Full cut	
Connectivity	- Mini-USB x 1	
Power Supply	 Serial (RS-232c) x 1 DC Power supply DC 24V ± 5% / TYP 2.7A 	
Dimensions	127 x 145.5 x 85.4 mm (W x D x H)	
Weight	Approx. 0.63 kg (without paper roll)	
Barcode Supported	1D : UPC-A/E, JAN13/8, CODE39, CODE93, ITF, CODABAR, CODE128, GS1 Databar Omni-directional, Truncated, Limited, Stacked, Stacked Omni-directional	
	2D : QR Code, MaxiCode, PDF417, Data Matrix	
Reliability	Print Head : 150 Kilometer	
	Auto Cutter : 2 million cuts	

SK1-311 Option List













Bezel Presenter Large Paper Holder HL1 Large Paper Holder HL2 Large Paper Holder HL3 Large Paper Holder HL4

