

SK4-21 is Star Kiosk two-inch model with compact design and 3 ways of paper position setup that can match many kind of kiosk environment even in very compact limitation All SK4 series come with Serial RS-232C and Mini-USB interfaces which integrate with many commonly used kiosk solutions.



**Sensor Support** 

SK4 Series come with Paper End sensor, Near End sensor and Black Mark sensor.



Flexible Installation

SK4 Series can match with various installation by wide range adjustable paper guide and very compact size







## **Dual Interface** Support



Serial Interface



Mini-USB interface

Adjustable



## **Best for Compact** Paper Holder





## SK4-21 Specifications

| Printer Model SK4-21  Printer Method Direct Thermal Line Printing  Emulation ESC/POS  Print Speed Max. 150 mm/second |  |  |
|--|--|--|
| Emulation ESC/POS  |  |  |
|  |  |  |
| Print Speed Max. 150 mm/second   |  |  |
|  |  |  |
| Resolution 203 dpi (8 dot/mm)  |  |  |
| Print Width 54 mm  |  |  |
| Paper Type Thermal Paper Roll  |  |  |
| Specifications Paper Width 58 mm   |  |  |
| Roll Diameter Max. Ø 83 mm (200mm with option  | n)   |  |
| Thickness 59 μm  |  |  |
| Auto-Cutter Partial cut (Leave center point) / Full cut  |  |  |
| Connectivity - Mini-USB x 1  |  |  |
| - Serial (RS-232c) x 1   |  |  |
| Power Supply DC 24V ± 5% / TYP 2.7A  |  |  |
| Dimensions 86 x 150 x 81.7 mm (W x D x H )   |  |  |
| Weight Approx. 0.35 kg (without paper roll)  |  |  |
| Barcode Supported 1D : UPC-A/E, JAN13/8, CODE39, CODE93, ITF, CODABAR,   |  |  |
|  | CODE128, GS1 Databar Omni-directional, Truncated, Limited, |  |
| Stacked, Stacked Omni-directional  |  |  |
| 2D : QR Code, MaxiCode, PDF417, Data Matrix  |  |  |
| Reliability Print Head : 100 Kilometer   |  |  |
| Auto Cutter : 1 million cuts   |  |  |







